EV03[®] LINESMAN MICRO PEAK - WHEEL RATCHET - NON-VENTED

PRODUCT CODE: AJG240-00 - 00

EVO3® IS A TRUE EVOLUTION OF THE LONG ESTABLISHED MK2® & MK3® HELMETS

TECHNICAL SPECIFICATION

HEAD PROTECTION

SHELL: UV Stabilised High Density Polyethylene (HDPE)

INSTRUCTIONS FOR USE

Fit helmet on head and fasten strap to ensure fit

For adequate protection this helmet must be worn with peak facing forward

Ensure the helmet is adjusted to the size of the user's head

CHAMLON™ SWEATBAND:

Egyptian cotton core with porous PU coating for maximum sweat absorption. PH neutral, dermatologically tested

WHEEL RATCHET:

The Revolution[®] Wheel Ratchet RE is the new easy to use wheel ratchet adjustment system to create a firm comfort fit with added security



CONFORMITY

Conforms to EN397, EN50365 & ANSIZ89

- EN 50365 for Helmets for use in low voltage installations
- EC Certificate Number 676976, issued by BSi Product Certification

Meets the retro reflective performance requirements of EN12899 when fitted with CR2 Reflective Kit

- Meets optional Molten Metal Splash performance
- Meets optional Electrical Insulation requirements
- Available vented or unvented. Available with mid or micro peak

Company personalisation available by printing

WEBBING HARNESS: HDPE Strap & Webbing Clips with Polyester Webbing Straps

CLEANING & MAINTENANCE

The unit may be cleaned with soap and warm water and dried with a soft cloth

The helmet should not be cleaned with chemical or abrasive cleaners

The helmet should be stored out of direct sunlight

The helmet should be stored away from chemicals and extremes of temperature



MANUFACTURING FOR SAFETY UKSALES@JSPSAFETY.COM <u>WWW.JSPSAFETY.COM</u> TEL: +44 (0)1993 826050

EV03[®] LINESMAN MICRO PEAK - WHEEL RATCHET - NON-VENTED

PRODUCT CODE: AJG240-00 - 00

EVO3® IS A TRUE EVOLUTION OF THE LONG ESTABLISHED MK2® & MK3® HELMETS

HEAD PROTECTION

SPECIFICATION

TECHNICAL

DIMENSIONS OF OUTER PACKAGING

Quantity:	10
Weight:	3.8kg (Approx.)



DIMENSIONS OF HELMET

Size: 530 - 640mm Weight: 375g (Approx.)



HELMET COLOURS

Insert the following two digit number in place of the dashes in the product code of your desired helmet



HELMET FEATURES EN397 EN Yes STANDARD EN50365 Yes PERFORMANCE Impact Resistance Yes 50 Joules

	Electrial Insulation	Yes: EN397 440v EN50365 1000v
TEMPERATURE RESISTANCE	Molten Metal (MM) -40°C	Yes Yes
SHELL MATERIAL	HDPE Recyclable UV Stabilised	Yes Yes Yes
HARNESS MATERIALS	HDPE LDPE Textile	Yes Yes Yes
OPTIONS	Universal Accesories Reflective CR2 option Integrated Eyewear Micro Peak	Yes Yes Yes Yes
HARNESS SYSTEM OPTIONS	JSP 3D Wheel Ratchet 6 pts	Yes Yes Yes
CHINSTRAP	4 pts	Yes
LOGO OPTIONS	Front Rear Side MOQ Logo	Yes Yes Yes 10

LIMITATIONS OF USE

Protection will only be offered if the helmet is fitted correctly

Any helmet subjected to severe impact should be replaced immediately. Do not apply paint, solvents or adhesive labels except in accordance with instructions from the manufacturer

The harness, when in contact with the skin may cause allergic reactions to susceptible individuals. If this occurs leave the hazard area, remove the helmet and seek medical advice

The attention of users is also drawn to the dangers of modifying or removing any of the original component parts, other than as recommended by the manufacturer



MANUFACTURING FOR SAFETY <u>www.jspsafety.com</u>

UKSALES@JSPSAFETY.COM TEL: +44 (0)1993 826050

