$\textbf{RIGI}^{\top M}$



The best seller of the coming decade..!

Whatever your workplace environment, Rigi™ delivers the perfect association of performance, safety and active style.

The unique close fitting design, ultra light weight... 19gr of comfort and fit. wide field of vision and a design fitting all faces... The ergonomic fit with Flexofit™ temples, flat and thin compatible with any eardefender or helmet. Those features enable wearers to achieve a comfortable customised fit, throughout the day. Try it... adopt it!

Available in a wide range of lens versions... Anti-scratch, Excellence coating and a unique selection of Blue Blocker lenses.

WEIGHT 19g

LENS

- Large field of vision
- Wide range of lenses
- Optimal coverage













FRAME

- Ultra lightweight
- Flex Flat, thin temple
- Pressure free









1RIG21C

1RIGLABB21AR

BLUE BLOCKER



- + ONE FITS ALL
- + Wraparound design





1RIG21S Smoke



1RIGBB21AR BLUE BLOCKER



1RIG23CKN Clear ≥



1RIGBB21LO BLUE BLOCKER



1RIG23SKN Smoke ≥



1RIGBB21LB BLUE BLOCKER 60% filtration

Reference	Lens Markings	Frame Markings	Lens Treatment	Conformity	
1RIG21C	2C-1,2 1 FT CE	● EN 166 FT CE	Anti-scratch	EN 166 EN 170	
1RIG21S	5-2,5 1 FT CE	● EN 166 FT CE	Anti-scratch	EN 166 EN 172	_
1RIG23CKN	2C-1,2 > 1 FTKN CE	● EN 166 FT CE	Anti-scratch / Anti-fog (KN)	EN 166 EN 170	Conforms to
1RIG23SKN	5-2,5 1 FT KN CE	● EN 166 FT CE	Anti-scratch / Anti-fog (KN)	EN 166 EN 172	EN 166: 2001 EC Type Examination
1RIGLABB21AR	2C-1,2 > 1FT CE	EN 166 FT CE	Anti-scratch	EN 166 EN 169	Certificate Number O958 Issued by Inspec
1RIGBB21AR	2C-1.2 → 1FT CE	● EN 166 FT CE	Anti-scratch	EN 166 EN 166	
1RIGBB21LO	2C-1,4 >>> 1FT CE	● EN 166 FT CE	Anti-scratch	EN 166 EN 168	
1RIGBB21LB	2C-1,4 >> 1FT CE	● EN 166 FT CE	Anti-scratch	EN 166 EN 167	_

For Lens & frames markings details, please refer to pages 7 to 9 in Swiss one catalogue. For Lens technologies and colors details please refer to pages 10 to 12 in Swiss one catalogue.





DIMENSIONS OF SPECTACLE

Lens Thickness:	1.8mm
Lens Base:	9.5
Lens Size (Diagonal):	70.5mm
Bridge:	-
Temple Length (Lens to tip):	162.0mm
Overall Width:	133.0mm
Closest point between temple tips:	31 +/- 3mm

1

- 1 Polycarbonate
- 3 PC/TPE
- 2 Polycarbonate

4 PC/TPE

INSTRUCTIONS FOR USE

- In use ensure that the safety spectacles fit comfortably and securely on the head
- Ensure that the safety spectacles are in place, before entering the hazard area

CLEANING & MAINTENANCE

- The safety spectacles may be cleaned with soap and warm water and dried with a soft cloth
- Do not clean with chemical or abrasive cleaners
- The eye shield should be stored out of direct sunlight, away from chemicals and not exposed to extremes of temperature

LIMITATIONS OF USE

- Protection will only be offered if the safety spectacles are fitted correctly
- If the safety spectacles become scratched or damaged they should be replaced, likewise if the safety spectacles are subjected to severe impact they should be replaced immediately
- Do not apply paint, solvents, adhesives or self-adhesive labels, except in accordance with instructions from the manufacturer
- The safety spectacles, when in contact with the skin may cause allergic reactions to susceptible individuals. If this occurs leave the hazard area, remove the eye shield and seek medical advice
- The attention of users is also drawn to the dangers of modifying or removing any of the original component parts, other than as recommended by the manufacturer
- Rigi™ is not suitable for protection against dusts, liquids or molten metals

DIMENSIONS OF INNER PACKAGING

Quantity:	10
Weight:	0.48kg



- H Height: 96mm
- L Length: 191mm
- W Width: 284mm

DIMENSIONS OF OUTER PACKAGING

Quantity: (30 display boxes of 10 p)	300
Weight: (Approx.)	16.4kg



- H Height: 63cm
- L Length: 98.5cm
- W Width: 30cm

Reference	EAN barcode Unit	EAN barcode inner packaging	EAN barcode outer packaging	Country of origin
1RIG21C	5038428303002	5038428303019	5038428303026	Taiwan
1RIG21S	5038428303033	5038428303040	5038428303057	Taiwan
1RIG23CKN	5038428303064	5038428303071	5038428303088	Taiwan
1RIG23SKN	5038428303095	5038428303101	5038428303118	Taiwan
1RIGLABB21AR	5038428303125	5038428303132	5038428303149	Taiwan
1RIGBB21AR	5038428303156	5038428303163	5038428303170	Taiwan
1RIGBB21LO	5038428303187	5038428303194	5038428303200	Taiwan
1RIGBB21LB	5038428303217	5038428303224	5038428303231	Taiwan