

TOUTRAVO VE511



NEOPRENE GLOVE - LENGTH 38 CM

Ref. VE511



Product specifications

Neoprene on cotton knitted lining gauge 10. Length: 38 cm. Thickness 1,40 mm.

Support: cotton.

Coating: Neoprene.

Foam finish.

Tested according to EN374-3:2003 determination of permeation resistance, levels of permeation from 1 to 6 (K : Sodium hydroxyde 40% (NaOH) = 6/6, L: sulphuric acid (96%) =4/6, J : n-Heptane = 2/6).

COLOUR

Black

SIZE

9/10, 10/11

Product Use - Risks



Heat



Biological chemical particles



Wearing



Construction / Civil engineering




Heavy industry



Oil / Gas



Mining



Product's highlights & user's benefits



Cotton knit gauge 10

Absorption of perspiration and moisture for improved comfort in everyday life

Neoprene

Versatile and highly efficient material against heat, detergents, alcohols, chemicals, greases and hydrocarbons

Certifications and Standards



REGULATION (EU) 2016/425

EN420:2003+A1:2009 General requirements
5: Dexterity (from 1 to 5)

EN388:2016 Protective gloves against mechanical Risks (Levels obtained on the palm)
2: Resistance to abrasion (from 1 to 4)
1: Resistance to cutting (from 1 to 5)
3: Resistance to tear (from 1 to 4)
2: Resistance to puncture (1 to 4)
X: Resistance to cutting by sharp objects (TDM EN ISO 13997) (from A to F)



EN ISO 374-1:2016 Protective gloves against dangerous chemicals and micro-organisms -
Part 1: Terminology and performance requirements for chemical risks.

TYPE A: Type A - Water and air tightness according to EN374-2:2014. Permeation resistance to at least 6 chemicals at level 2 according to EN16523-1: 2015, .. Determination of resistance to degradation by chemicals according to EN374-4: 2013. Part 4: Determination of resistance to degradation by chemicals.





A 6 > 480 mn: Méthanol (A) CAS 67-56-1
J 3 > 60 mn: n-Heptane (J) CAS 142-85-5
K 6 > 480 mn: Caustic soda 40% (K) CAS 1310-73-2
L 5 > 240 mn: Sulphuric acid 96 % (L) CAS 7664-93-9
M 6 > 480 mn: Nitric acid 65% (M) CAS 7697-37-2
N 6 > 480 mn: Acetic acid 99% (N) CAS 64-19-7
O 6 > 480 mn: Ammonium hydroxide 25% (O) CAS 1336-21-6
P 6 > 480 mn: Hydrogen peroxide 30% (P) 7722-84-1
T 6 > 480 mn: Formaldehyde 37% (T) CAS 50-00-0

EN ISO 374-5:2016 Protective gloves against dangerous chemicals and micro-organisms -
Part 5: Terminology and performance requirements against micro-organisms risks.

BACTERIA + FUNGI : BACTERIA + FUNGI : Water and air tightness according to EN374-2:2014.



References

References	Bar code	COLOUR	SIZE		
VE511NO09	3295249187675	Black	9/10	60	12
VE511NO10	3295249187682	Black	10/11	60	12