TECHNICAL SPECIFICATION



K2[™] 5-Point Harness

K2™ 5-Point Harness / FAR0403



DESCRIPTION

The premium $K2^{TM}$ harness range combines quality materials with innovative features for optimum ergonomic performance, comfort, and safety.

Riggers harness with ventral and lateral attachment points, made from breathable air mesh material and lightweight alloy steel and aluminium hardware to ensure comfort and safety throughout extended wear.

OPTIONS

K2™ 5-Point Harness (FAR0403)

SAFETY STANDARDS

EN 361 • EN 358 • EN 813















SPECIFICATIONS

Anchorage Points

2

Fall Indicator

No

Work Postioning Belt

Yes

Lanyard Parking

Yes

Sub-Pelvic Strap

Yes

Metal Parts

Light Alloy Steel



Product Weight

2410g

Adjustment

Shoulders, Chest and Legs

Quick Release Buckles

Yes

Tool Keeper

Yes

Comfort Padding

Yes

Product Label Protected



Rated Weight / Load

140kg

FEATURES



Quick Release Buckles

Quick release buckles for quick and effortless fitting.



Tool Keepers

K2™ 3-point and 5-point harnesses feature tool keepers for safely stowing tools.



Lanyard Keepers

Breakaway clips safely store unused lanyards and release in the event of a fall.



Breathable Material

Air mesh material gives harnesses breathability and anti-tangle feature.



Inspection Labels

Inspection labels and user information protected in PVC pouch.



Ultimate Comfort

Polyester padding in leg, back and waist areas for improved comfort.

RANGE **VIDEOS**



youtu.be/YjvDWkFh0Vc

DOWNLOADS





doc-far0401-far0402-far0403.pdf (PDF)





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com





